Protectors

COLOUR ENHANCER MATT FINISH

Colour-enhancing, stain-proof impregnator with matt wet-look finish, for all absorbent surfaces

COLOUR ENHANCER MATT FINISH is a solvent-based, colour-enhancing and stain-proof impregnating agent that penetrates the surface without filming. It leaves a matt wet-look finish and ensures great protection against stains on all medium-absorbent materials with non-polished finish

The formula of **COLOUR ENHANCER MATT FINISH** gives treated material a matt wet look while enhancing the colour and tone without creating a surface film. This product also stands out for its excellent water-repellence and stain-proof qualities, which offer effective protection against stains, and the damaging effects of water.

COLOUR ENHANCER MATT FINISH has a guaranteed, lasting colour-enhancing, protective effect and is the ideal solution to treat surfaces and objects, even outside, thanks to its excellent resistance to bad weather and to UV rays. It can also be used on surfaces that, due to their nature need to remain in continued contact with water: showers, fountains, washbasins and even kitchen counter tops, since the product is certified for contact with foods.

COLOUR ENHANCER MATT FINISH also makes routine surface maintenance easier, as it limits a surface's ability to trap dirt, preventing dirt and stains from penetrating below the surface and attaching to the material.

COLOUR ENHANCER MATT FINISH is ready to use and quick and easy to apply. It is suitable for all types of absorbent material and can be used indoors and outside. **COLOUR ENHANCER MATT FINISH** is not suitable for use on non-absorbent materials or on materials with a polished finish

CHARACTERISTICS AND BENEFITS

- ✓ **Strong colour-enhancing capacity**
- ✓ Penetrates deep inside the material
- ✓ **Leaves** surfaces **stain proof**
- ✓ **Enhances the material's tone and colour**
- ✓ **Ultra resistant over time**
- ✓ Excellent **water- and oil-repellent characteristics**
- ✓ **Resistant to UV rays**
- ✓ **Will not yellow** over time
- ✓ **Adds a matt finish**
- ✓ **Will not create a surface film**
- ✓ **Also suitable for application outdoors.**
- ✓ **Certified for food use**
- ✓ **Ideal for application on wet areas (saunas, showers, washbasins, fountains)**

FABERSURFACECARE.COM

FABER CHIMICA SRL – VIA G.CERESANI, 10 – LOC.CAMPO D'OLMO – 60044 – FABRIANO (AN) – **ITALY**
Phone: +39 0732 627178 | **Fax**: +39 0732 22935 | **Email**: info@faberchimica.com

Protectors

COLOUR ENHANCER MATT FINISH- Impregnating

toning and stain-proof agent with matt wet-look, for all absorbent surfaces

USES

This product **can be used** on both indoor and outdoor surfaces.

Suitable for use on: Marble-resin agglomerate, Quartz-resin agglomerate, Slate, Sandstone, Basaltina - Lava rock, Molten basalt, Cementina, Concrete, Cotto, Granite, Limestone, Marble, Reconstituted (eco) stone, Porphyry, Quarzite, Terracotta, Travertine, and Tuff.

This product **is not suitable** for use on non-absorbent surfaces or materials with polished finish

COVERAGE

10-15 m^2/l according to the absorption level of the surface being treated

APPLICATION EQUIPMENT

Brush, roller, lambswool applicator, airless spray, cloth

APPLICATION STEPS

Preparing and cleaning the surface

1. Carefully clean the surface, making sure to remove any dust or dirt present.
2. Wait for the surface to be treated to be completely dry.
3. Any adjacent surfaces not being treated with the product must be protected.

Application

Before applying the product to the whole surface, always test a small, unexposed area or unused piece to check its suitability for use.

4. Apply a thick, even layer of product to cover the whole surface being treated, using the tools of choice. Make sure to create a layer that is as seamless and even as possible.
5. About 10 minutes from application, make sure there are no residues or excess product on the surface, and redistribute these as necessary, evening the coverage until they are completely removed.
6. If applying the product to more absorbent surfaces, apply a second coat about 1-2 hours after the first, following the same procedure described above.

At the end of the operation, do not wash the floor for 24 hours after treatment. Extending this period to 48 hours, gives the product time to attach itself firmly to the surface, which will extend its duration.

Drying time

Surfaces will be dry about 1-2 hours from product application.

Opening to floor traffic

When used on floor surfaces, wait at least 6 hours before opening the floor to foot traffic.

COMPLEMENTARY CLEANING AND MAINTENANCE PRODUCTS

After treatment with COLOUR ENHANCER MATT FINISH, maintain the surface clean with the product most suitable Faber product , such as NEUTRAL CLEANER or FLOOR CLEANER or , to be chosen according to the surface characteristics.

FABERSURFACECARE.COM

FABER CHIMICA SRL – VIA G.CERESANI, 10 – LOC.CAMPO D'OLMO – 60044 – FABRIANO (AN) – **ITALY**
Phone: +39 0732 627178 | **Fax**: +39 0732 22935 | **Email**: info@faberchimica.com

COLOUR ENHANCER MATT FINISH- Impregnating

toning and stain-proof agent with matt wet-look, for all absorbent surfaces

INSTRUCTIONS AND GUIDELINES

- Never apply the product to a wet surface
- Do not apply the product to overly heated surfaces
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- If used after a water-repellent primer has been applied, wait for this treatment to cure fully before applying COLOUR ENHANCER MATT FINISH
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be cleaned using white spirit.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

PHYSICAL AND TECHNICAL INFORMATION

DATI FISICO-TECNICI	
Aspect:	Liquid
Colour	Transparent
Odour	White spirit
Specific gravity at 20°C	800 ± 10 g/l
Flash point (ASTM D 56)	30°C vaso aperto

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

ACCIDENTAL SPILLS

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.

PACKAGING

- 1 l bottles - 12 bottles per box
- 5 l cans – 4 cans per box

FABERSURFACECARE.COM

FABER CHIMICA SRL – VIA G.CERESANI, 10 – LOC.CAMPO D'OLMO – 60044 – FABRIANO (AN) – **ITALY**
Phone: +39 0732 627178 | **Fax**: +39 0732 22935 | **Email**: info@faberchimica.com

HAZARD IDENTIFICATION

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness
EUH066	Repeated exposure can cause skin dryness and cracking.
P210	Keep far from heat sources / sparkles / free flames / heated surfaces. Do not smoke.
P261	Avoid breathing dust / fume / gas / mist/ vapours /spray.
P331	DO NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Remove contaminated clothing. Rinse skin/take a shower.

Version 3.0 – 01/09/2016

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

FABERSURFACECARE.COM

FABER CHIMICA SRL – VIA G.CERESANI, 10 – LOC.CAMPO D'OLMO – 60044 – FABRIANO (AN) – **ITALY**
Phone: +39 0732 627178 | **Fax**: +39 0732 22935 | **Email**: info@faberchimica.com