

WAX REMOVER

Alkaline-based wax stripper for deep removal of greasy dirt, old treatments and existing layers of wax.



WAX REMOVER is an alkaline-based wax stripper for deep removal of organic dirt, greasy surface stains, and greasy dirt, even if stubborn or old. It is also effective on mould, algae and bio residues. It can also be used to remove existing surface treatments and old layers of wax.

WAX REMOVER can be used in combination with the *SOLVENT STRIPPER* for even deeper cleaning to carry out “double wax stripping”.

WAX REMOVER can be used - if correctly diluted - on all types of floor or surface. Recommended to remove cement residues from acid-sensitive materials.

CHARACTERISTICS AND BENEFITS

- ✓ A versatile product, suitable for use on different types of material
- ✓ Ready to use
- ✓ Top-level cleaning action
- ✓ Effective on organic-based residues
- ✓ Removes stains and greasy or oily dirt.
- ✓ Removes old wax and existing treatments
- ✓ Quick and easy application

USES

This product **can be used** on both indoor and outdoor surfaces.

Suitable for use on: Marble-cement agglomerate, Marble-resin agglomerate, Marble-quartz agglomerate, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Cementina, Concrete, Craquelé ceramics, Glazed ceramics, Clinker, Cotto, Granite, Lapped porcelain stoneware, Polished porcelain stoneware, Natural porcelain stoneware, Textured porcelain stoneware, Limestone, Marble, Reconstituted stone (Eco stone), Porphyry, Quarzite, Terracotta, Travertine, Tuff

COVERAGE

10/15 m²/l

APPLICATION EQUIPMENT

Cloth, mop, single disc machine

APPLICATION STEPS FOR WAX REMOVER ONLY

Preparing and cleaning the surface

1. Before proceeding to wash the surface, it is advisable to clean away any surface residues, such as dust, debris and coarse dirt, using a broom or a vacuum cleaner.
2. Wait for the surface to be treated to be completely dry.
3. Any adjacent surfaces not being treated with the product must be protected.
4. Apply the product to surfaces with a temperature of between +5 and +40°C



Cleaners

WAX REMOVER - Alkaline-based wax stripper for deep removal of greasy dirt, old treatments and existing layers of wax.

Application

Before applying the product to the whole surface, it is always necessary to test a small, unexposed area or unused piece to check its suitability for use.

5. Dilute the product in clean water. Pour 1 part product into 4 parts water.
6. Begin to work the product over the surface, rubbing the surface with the tool of choice.
7. Leave the product to act for 5 - 10 minutes, continuing to wipe over the surface with your tool of choice to boost and aid the cleansing action of the product.
8. After working the product, remove all residues and rinse the whole floor with plenty of water. If the result is only partially achieved, repeat the application process following the same steps and if necessary, slightly increase the concentration of the product in water.

Drying time

9. After carefully removing any residues and rinsing the surface with water, no further action or waiting time is necessary.

Opening to floor traffic

10. After carefully removing any residues and rinsing the surface with water, the floor can be opened to foot traffic.

APPLICATION STEPS FOR DOUBLE WAX STRIPPING (Solvent Stripper + Wax Remover)

Preparing and cleaning the surface

1. Before proceeding to wash the surface, it is advisable to clean away any surface residues, such as dust, debris and coarse dirt, using a broom or a vacuum cleaner.
2. Wait for the surface to be treated to be completely dry.
3. Any adjacent surfaces not being treated with the product must be protected.
4. Apply the product to surfaces with a temperature of between +5 and +40°C

Application

Before applying the product to the whole surface, always test a small, unexposed area or unused piece to check its suitability for use.

5. Pour the *Solvent Stripper*, undiluted, straight onto the surface being treated.
6. Begin to work the product over the surface, rubbing the surface with the tool of choice.
7. Leave the product to act for 5 - 10 minutes, continuing to wipe over the grout with your tool of choice to boost and aid the cleansing action of the product and following the instructions on the technical data sheet for the product.
8. After the above time, without removing any product residues, pour the *Wax Remover* straight onto the surface, following the instructions above
9. Work the *Wax Remover* with a single-disc machine or broom, following the above instructions.
10. Once the product has been applied, proceed to remove all residues and rinse the surfaces, following the above instructions.



Cleaners

WAX REMOVER - Alkaline-based wax stripper for deep removal of greasy dirt, old treatments and existing layers of wax.

Drying time

9. After carefully removing any residues and rinsing the surface with water, no further action or waiting time is necessary.

Opening to floor traffic

10. After carefully removing any residues and rinsing the surface with water, the floor can be opened to foot traffic.

COMPLEMENTARY CLEANING AND MAINTENANCE PRODUCTS

After treating with WAX REMOVER, keep the surface clean with the most suitable Faber product, such as NEUTRAL CLEANER or FLOOR CLEANER, to be selected according to the characteristics of the surface.

INSTRUCTIONS AND GUIDELINES

- Wait at least 2 days after grouting before proceeding with the end of installation washing.
- Never apply the product to a wet surface
- Do not apply the product to overly heated surfaces
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Never use in conjunction with other chemical products unless expressly instructed to do so.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

SAFETY

When applying the product, always use suitable personal protective equipment and carefully follow the instructions on the product safety data sheet.

PHYSICAL AND TECHNICAL INFORMATION

Aspect:	Liquid
Colour:	Amber
Odour:	Typical
pH:	12 ± 0,5
Specific gravity at 20°C	1030 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

ACCIDENTAL SPILLS

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.



FABERSURFACECARE.COM



Cleaners

WAX REMOVER - Alkaline-based wax stripper for deep removal of greasy dirt, old treatments and existing layers of wax.



PACKAGING

- 1 l bottles - 12 bottles per box
- 5 l cans – 4 cans per box
- 10 l cans – loose cans

HAZARD IDENTIFICATION



H314	Causes severe skin burns and eye damage.
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P260	Do not breathe dust/fumes/gas/mist/vapours/spray.
P264	Wash hands and face thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): remove immediately all contaminated clothing. Rinse skin with water/shower.
P310	Immediately call a POISON CENTER or doctor/physician.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P501	Dispose of contents/container in collection areas for hazardous or special waste.

Version 5.0 – 17/12/2018

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

