

DEEP PROTECTOR

Solvent-based deeply penetrating water-repellent impregnating treatment. It's completely invisible and leaves no residues, it protects from the absorption of rising humidity and water.



DEEP PROTECTOR is an impregnating solvent-based treatment that provides anti-absorbing properties against rising humidity and water infiltrations. It's suitable for all absorbing surfaces made of natural stone, Cotto, brick, cement, clinker, ceramic, and porcelain tiles. **DEEP PROTECTOR** protects the treated surface against all the problems related to the absorption of rising humidity such as mold, salt efflorescences, humidity stains, and superficial detachments. **DEEP PROTECTOR** is characterized by its great ability to penetrate deep into the material on which it's applied, enabling the product to protect the surface of the material. This makes the product great to protect tiled cracked surfaces that otherwise would cause infiltration issues. **DEEP PROTECTOR** is completely invisible, it doesn't affect the original look and the shade of the treated surface. It doesn't create any superficial film cause, due to its penetrating abilities, the product can be easily absorbed into the material. It doesn't affect the breathability of the treated surface. **DEEP PROTECTOR** can also be used to protect porous and absorbing materials such as Cotto from grouting and cleaning operations. Its water-repellent action reduces drastically the water absorption and prevents grout stains to occur. **DEEP PROTECTOR** also makes ordinary maintenance easier due to the fact that the product reduces the ability of the surface to store dirt, stopping it from penetrating and settling in the texture of the surface. **DEEP PROTECTOR** can also be used as a water-repellent base before the application of superficial stain-proof treatments on top. **DEEP PROTECTOR** is ready to use and quick and easy to apply. It is suitable for all the absorbing materials indoor and outdoor.

CHARACTERISTICS AND BENEFITS

- ✓ **Great water-repellent ability:** it stops the absorption of rising humidity and water.
- ✓ **Highly penetrating**
- ✓ It Protects **tile joints, and cracks** preventing any infiltrations
- ✓ **Invisible treatment:** It doesn't affect the shade and the original look of the material
- ✓ **It doesn't alter the breathability** of the surface
- ✓ **UV and bad weather conditions** resistant
- ✓ It doesn't leave any **yellow stains** throughout the years
- ✓ **Suitable for all absorbing materials**
- ✓ **It can also be used** to protect the surface **before grouting**
- ✓ **Quick and easy application**

USES

This product **can be used** on both indoor and outdoor surfaces.

Suitable for use on all the absorbent materials: marble, granite, stone, concrete, cotto, ceramic, porcelain ceramic, clinker

COVERAGE

10-15 m²/l according to the absorption level of the surface being treated

APPLICATION EQUIPMENT

Brush, roller, lambswool applicator, spray, cloth



Protectors

DEEP PROTECTOR- Trattamento Impregnante idrorepellente di profondità in base solvente, completamente invisibile, per proteggere assorbimento, risalita ed infiltrazioni di acqua e umidità



APPLICATION STEPS

Preparation and surface cleaning

1. Proceed with cleaning the surface thoroughly from any traces of dust and dirt
2. Wait until the surface is completely dry
3. Protect the areas not to be treated.

Application

Before proceeding with the application of the product it's necessary taking a preliminary test on a portion of the surface to evaluate the result.

4. Evenly distribute a thick and even layer of product on the entire surface to be treated using the preferred tool. Pay attention to distribute quickly an even and continuous layer of product.
5. DEEP PROTECTOR dries rapidly thanks to its penetrating ability. Avoid leaving any product build-ups on the surface.
6. In case of a highly absorbing surface apply a second layer after an hour from the first application following the same procedure as previously described.

Drying time

Surfaces will be dry about 1 hour from product application.

Opening to floor traffic

When used on floor surfaces, wait at least 4-6 hours before opening the floor to foot traffic.

COMPLEMENTARY CLEANING AND MAINTENANCE PRODUCTS

After treatment with DEEP PROTECTOR, maintain the surface clean with the product most suitable Faber product , such as NEUTRAL CLEANER or FLOOR CLEANER or , to be chosen according to the surface characteristics.

INSTRUCTIONS AND GUIDELINES

- Never apply the product to a wet surface
- Do not apply the product to overly heated surfaces
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- If applied after using a water-repellent primer. In this case, wait for the primer to cure completely before applying DEEP PROTECTOR
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be cleaned using white spirit.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.



Protectors

DEEP PROTECTOR- Trattamento Impregnante idrorepellente di profondità in base solvente, completamente invisibile, per proteggere assorbimento, risalita ed infiltrazioni di acqua e umidità



PHYSICAL AND TECHNICAL INFORMATION

Aspect:	Liquid
Colour:	Colourelss
Odour:	Solvent
Specific gravity at 20°C	0.838 g/cm ³

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

ACCIDENTAL SPILLS

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.

PACKAGING

- 1 l bottles - 12 bottles per box

FABERSURFACECARE.COM



Protectors

DEEP PROTECTOR- Trattamento Impregnante idrorepellente di profondità in base solvente, completamente invisibile, per proteggere assorbimento, risalita ed infiltrazioni di acqua e umidità



HAZARD IDENTIFICATION



H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Do not allow contact with water.
P261	Avoid breathing dust/fume/gas/mist/vapours/ spray.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/ attention.
P370+P378	In case of fire: Use carbon dioxide or chemical powder or foam to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up
P501	Dispose of contents/container according to the local laws

Version 0.0 – 04/09/2019

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet. The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

