

SOLVENT STRIPPER

Solvent-based wax stripper for deep removal of greasy oxidation, wax and existing treatments



SOLVENT STRIPPER is a solvent-based wax stripper to use on deep cleaning of dirt and organic residues, oxidation, layers of old wax or existing treatments. Its action works deep down, helping to dissolve and easily remove even the most stubborn dirt and greasy or oily surface stains.

SOLVENT STRIPPER can be used in combination with *ALKALINE CLEANER* or *WAX REMOVER* for even deeper cleaning to carry out "double wax stripping". **SOLVENT STRIPPER** is suitable for all types of material, whatever its absorption level, indoors and out.

CHARACTERISTICS AND BENEFITS

- ✓ Excellent wax-stripping power
- ✓ High capacity to penetrate into the material
- ✓ Gentle on surfaces but effective against dirt.
- ✓ Ideal for removing oily dirt

USES

This product **can be used** on both indoor and outdoor surfaces.

Suitable for use on: Marble-cement agglomerate, Marble-resin agglomerate, Marble-quartz agglomerate, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Cementina, Concrete, Craquelé ceramics, Glazed ceramics, Clinker, Cotto, Granite, Lapped porcelain stoneware, Polished porcelain stoneware, Natural porcelain stoneware, Textured porcelain stoneware, Limestone, Marble, Reconstituted stone (Eco stone), Porphyry, Quarzite, Terracotta, Travertine, Tuff

COVERAGE

10/15 m²/l

APPLICATION EQUIPMENT

Cloth, mop, single disc machine

APPLICATION STEPS FOR SOLVENT STRIPPER ONLY

Preparing and cleaning the surface

1. Before proceeding to wash the surface, it is advisable to clean away any surface residues, such as dust, debris and coarse dirt, using a broom or a vacuum cleaner.
2. Wait for the surface to be treated to be completely dry.
3. Any adjacent surfaces not being treated with the product must be protected.
4. Apply the product to surfaces with a temperature of between +5 and +40°C



Cleaners

SOLVENT STRIPPER -Solvent-based wax stripper for deep removal of greasy oxidation, wax and existing treatments



Application

Before applying the product to the whole surface, it is always necessary to test a small, unexposed area or unused tile to check its suitability for use.

5. Pour the undiluted product straight onto the surface being treated.
6. Begin to work the product over the surface, rubbing the surface with the tool of choice.
7. Leave the product to act for 5 - 10 minutes, continuing to wipe over the surface with your equipment of choice to boost and aid its penetrating and cleansing action.
8. After working the product, remove all residues and rinse the whole floor with plenty of water. If the result is only partially achieved, repeat the application process following the same steps.

Drying time

9. After carefully removing any residues and rinsing the surface with water, no further action or waiting time is necessary.

Opening to floor traffic

10. After carefully removing any residues and rinsing the surface with water, the floor can be opened to foot traffic.

APPLICATION STEPS FOR DOUBLE WAX STRIPPING (Solvent Stripper + Wax Remover/Alkaline Cleaner)

Preparing and cleaning the surface

1. Before proceeding to wash the surface, it is advisable to clean away any surface residues, such as dust, debris and coarse dirt, using a broom or a vacuum cleaner.
2. Wait for the surface to be treated to be completely dry.
3. Any adjacent surfaces not being treated with the product must be protected.
4. Apply the product to surfaces with a temperature of between +5 and +40°C

Application

Before applying the product to the whole surface, always test a small, unexposed area or unused piece to check its suitability for use.

5. Pour the *Solvent Stripper*, undiluted, straight onto the surface being treated.
6. Begin to work the product over the surface, rubbing the surface with the tool of choice.
7. Leave the product to act for 5 - 10 minutes, continuing to wipe over the surface with your equipment of choice to boost and aid its penetrating and cleansing action.
8. After the above time, without removing any product residues, pour the alkaline wax stripper (*Wax Remover* or *Alkaline Cleaner*) straight onto the surface, following the instructions on the data sheet of the product being used.
9. Work the alkali wax stripper with a single-disc machine or broom, following the instructions on the data sheet of the product being used.
10. Once the product has been applied, proceed to remove all residues and rinse the surfaces, following the instructions on the data sheet of the product being used.



Cleaners

SOLVENT STRIPPER -Solvent-based wax stripper for deep removal of greasy oxidation, wax and existing treatments

Drying time

9. After carefully removing any residues and rinsing the surface with water, no further action or waiting time is necessary.

Opening to floor traffic

10. After carefully removing any residues and rinsing the surface with water, the floor can be opened to foot traffic.

COMPLEMENTARY CLEANING AND MAINTENANCE PRODUCTS

After treating with SOLVENT STRIPPER, keep the surface clean with the most suitable Faber product, such as NEUTRAL CLEANER or FLOOR CLEANER, to be selected according to the characteristics of the surface.

INSTRUCTIONS AND GUIDELINES

- Never apply the product to a wet surface
- Do not apply the product to overly heated surfaces
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- When applying indoors, ventilate the room thoroughly during use.
- Never use in conjunction with other chemical products unless expressly instructed to do so.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

PHYSICAL AND TECHNICAL INFORMATION

Aspect:	Liquid
Colour:	Transparent
Odour:	Organic Solvent
pH:	n.a.
Specific gravity at 20°C	800 ± 10 g/l
Flash point	30°C open vase

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

ACCIDENTAL SPILLS

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.



Cleaners

SOLVENT STRIPPER -Solvent-based wax stripper for deep removal of greasy oxidation, wax and existing treatments



PACKAGING

- 1 l bottles - 12 bottles per box
- 5 l cans – 4 cans per box

HAZARD IDENTIFICATION



H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../equipment.

Version 3.0 – 5/09/2016

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

